

## Safe Work Procedure – Cable Yarding – Landingman

---

**PERSONAL PROTECTIVE EQUIPMENT:**      Hi-vis Hardhat  
Hi-vis Vest  
Hearing Protection  
Eye Protection  
Leg Protection  
Caulked Boots

**RESPONSIBILITY TO OTHERS:**

- Is responsible for the safety of himself and all others in or around the landing.
- Is responsible for directing traffic into or through the landing.
- Is responsible for directing the landing of logs when necessary.

**CHASING:**

- Keep in the clear of the turn when it is being landed (safe zone).
- Be sure logs are stable before going in to unhook them.
- Unhook bottom logs first and from the upper side when applicable.
- Never stand under the yarding lines when a turn is being yarded.
- Inspect the butt rigging regularly and report badly worn parts.
- Replace badly kinked and jagged chokers.
- Ensure the yarder operator and loaderman know where you are at all times.
- Do not use gas to light fires.
- Keep landing area neat and tidy and equipment in good condition.

**GENERAL:**

- Do not look directly at the line when cutting.
- Use a soft hammer when cutting the line.
- Use eye protection when cutting the line.
- Use caution when using sharp tools.
- Wear leg pads whenever using a power saw.
- Adequate training is required by a qualified person before using a power saw.
- Check chokers for jaggars.

**ADDITIONAL SWP NOTES**

---

---

---

---