



**LOG TRUCK LOADING:**

- If the deck is beside the truck, logs shall not be picked up from it until the driver and/or other workers have finished their duties and have moved to the safe zone.
- Loading shall cease at any time that the loader operator is uncertain that the driver is in the cab or is in the clear in front of the truck.
- When approaching a truck with a grapple full of logs, avoid traveling with the grapple at full height. Keep the grapple low until near the truck, then raise the grapple. This will ensure better control of the loader at all times.
- Logs shall be loaded to ensure the stability of the vehicle and load while in transit.
- Logs shall be well positioned in their lay, without crowding, to avoid excessive strain on the stake-liner and stakes.
- To ensure stakes remain at a safe angle, logs shall be laid tight to minimize slack in the stake cables.
- Bunk and stake logs shall extend at least 12 inches (30cm) beyond the bunks or stakes.
- Logs shall be loaded clear of the bulkhead to avoid being bunk-bound on corners.
- When loading small diameter logs, two tiers should be used as bunk and stake logs before loading short logs onto the load.
- Never place split, cracked or shattered logs on the bunk or against the stakes.
- Not more than one third of the weight of the logs shall extend beyond the trailer or beyond the ends of the logs supporting them.
- Care should be taken to properly balance the load, especially on off-highway trucks. A side heavy load or a load with too much weight on the trailer could cause a truck to tip over or “spin-out” under wet or icy conditions.
- Workers are not permitted to stand on the cab platforms of trucks when loading by conventional methods. If this occurs, the loader operator shall cease loading until the worker is removed.
- Operators shall ensure that all workers are safely in the clear before initiating or continuing the motion of any mobile equipment.
- Although operators are responsible, it is also the responsibility of buckers and other workers to stay clear of any area considered to be hazardous due to the movement of such equipment.
- There must be a specific procedure for all equipment and vehicle operators, to allow safe movement through active log landings. Landing workers in charge of traffic control shall be thoroughly instructed in this procedure.
- Truck drivers must wear a hi-vis orange or red hard hat and a hi-vis clothing at all times when within the boundaries of the logging area.
- The truck driver must not move his load until the load has proper binders attached.

